

Prelude XL 32 24mm FLAT FACE

800型 24mm平面龙骨



MAYEE™ RH90 with Prelude XL 32 24mm Exposed Tee Grid
美翊™RH90 配 800 型 24mm 明架龙骨

BENEFITS

主要特性：

- Hot dipped galvanized coating inhibits red rusting better than electrogalvanized, painted or tin plated systems
热镀锌龙骨防锈蚀能力远胜于电镀锌，喷漆或镀锡龙骨
- Rotary stitched for additional torsional strength and extra stability during installation
旋转咬合的专利设计，增加额外的抗扭强度，确保安装稳定性
- Tighter tee to tee connection of XL cross tee
XL副龙骨之间连接更牢固
- Easy to remove and relocate
易于拆卸及再次安装
- System is engineered and designed to fit and provide a finish to coordinate with all of Armstrong Ceilings
龙骨系统的安装及设计使之能与阿姆斯壮天花板完美配合并提供和谐一致的表面颜色

Inspiring Great Spaces™

创想·天地™

Armstrong®

CEILING SYSTEMS

Prelude XL 32 24mm FLAT FACE 800型 24mm平面龙骨

Prelude XL 32 24mm Flat Face 800型 24mm平面龙骨						
	Item 产品代码	Description 产品描述	Dimensions 名义尺寸			
			Rout Spacing 槽口间距	Length 长度	Height 高度	Width 宽度
	BP7342101C*	Main Beam: Flat Faced 24mm Tee (C3 Coupling Connection) 主龙骨: 24mm平面龙骨 (一体式接头)	150mm	3000mm	32mm	24mm
	BP7347101C*		6"	120"	1-1/4"	15/16"
	BP313061	Cross Tee: Flat Faced 24mm Tee (XL Clip Connection - override with Main Beam) 副龙骨: 24mm平面龙骨 (XL钢接头 - 与主龙骨搭接)	600mm	1200mm	27mm	24mm
	XL7147WH		24"	48"	1-1/16"	15/16"
	BP312011	Cross Tee: Flat Faced 24mm Tee (XL Clip Connection - override with Main Beam) 副龙骨: 24mm平面龙骨 (XL钢接头 - 与主龙骨搭接)	-	600mm	25mm	24mm
	XL7124WH		-	24"	1"	15/16"

Wall Molding 边龙骨

	BPT1935H	Std "L" Angle Molding 标准L型边龙骨	-	3000mm	19mm	19mm
--	----------	----------------------------------	---	--------	------	------

*Load 承载: 8.12kg/m LD

Note: HANGER SPACING 吊筋跨度 1200mm



SCAN THIS CODE to learn
more about Suspension Systems

扫描二维码,
获取详细的产品信息

www.armstrong-asia.com
www.armstrong.cn

免费咨询热线: 400-779-3366

09-2015 Printed in Shanghai

Inspiring Great Spaces™

创想·天地™

Armstrong®

CEILING SYSTEMS