

# PRELUDE® Plus XL® Fire Guard™

## PRELUDE® XL® for Exterior Applications

### Exposed Tee System



UP TO **30%** RECYCLED CONTENT

Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

LEED®	energy management	construction waste to reuse	regional materials	design for flexibility	EPD	recyclable/extended producer resp.	bio-based materials	recycled content	sourcing of raw materials	material ingredient reporting	low emitting materials	lighting quality	acoustics
-------	-------------------	-----------------------------	--------------------	------------------------	-----	------------------------------------	---------------------	------------------	---------------------------	-------------------------------	------------------------	------------------	-----------

LOCATION DEPENDENT

A 15/16" suspension system for severe environmental performance.



Prelude® Plus XL® suspension system

#### KEY SELECTION ATTRIBUTES

- **Seismic Rx®** Suspension System saves time and money; ICC-ES approach to installations (ESR-1308)
- Prelude® Plus XL® Fire Guard™ and Prelude® XL® for Exterior Applications are part of the Sustain™ portfolio and meets the most stringent sustainability compliance standards today – White only
- Systems conform to ASTM C635 for Severe Environmental Performance
- Rotary-stitched during manufacture for torsional strength and stability
- 10-Year Limited Warranty; 30-Year Limited Warranty with **HumiGuard® Plus** or **HumiGuard® Max** products
- XL® staked-on end detail provides secure locked connection
- **PeakForm®** profile increases strength and stability
- **SuperLock™** main beam clip engineered for secure connection and fast, accurate alignment
- 10-Year replacement items available




#### COLORS

##### Fire Guard™



##### Exterior



#### PRELUDE® XL® For Exterior Applications

- Minimum G90 hot-dipped galvanized steel with prefinished G90 steel capping
- Suitable for wind uplift applications with appropriate bracing

#### PRELUDE® Plus XL® Fire Guard™

- Systems are minimum G60 hot-dipped galvanized steel with prefinished aluminum capping for enhanced corrosion resistance

#### TYPICAL APPLICATIONS

##### PRELUDE Plus XL Fire Guard

- Locker rooms
- Food preparation areas

##### PRELUDE XL For Exterior Applications

- Non-exposed exterior corridors
- Drive-thru areas
- Indoor parking garages
- Use with Woodworks® Linear Solid Wood Panels for Exterior

#### VISUAL SELECTION

Face Profile	Item No. ♦	Description	Dimensions (Inches)	Hanger Spacing* Lbs./LFT		
				2 Ft.	4 Ft.	5 Ft.
<b>Prelude® Plus XL® Fire Guard™ (Red Numbers are Fire Guard Items)</b>						
15/16"	<b>HD8201</b> _ _	12' HD Main Beam	144 x 15/16 x 1-11/16"	12.75	16.73	–
15/16"	<b>XL8240</b> _ _	4' Cross Tee	48 x 15/16 x 1-1/2"	12.75	–	–
15/16"	<b>XL8223</b> _ _	2' Cross Tee	24 x 15/16 x 1-1/2"	38.63	–	–
<b>Molding</b>						
7/8"	<b>HD7801</b> _ _	10' Hemmed Angle Molding	120 x 7/8 x 7/8"	–	–	–
<b>Prelude XL for Exterior Applications</b>						
15/16"	<b>7301G90A</b> _ _	12' HD Main Beam	144 x 15/16 x 1-11/16"	–	16.50	6.92
15/16"	<b>XL7341G90A</b> _ _	4' Cross Tee	48 x 15/16 x 1-11/16"	–	16.59	–
15/16"	<b>XL7321G90A</b> _ _	2' Cross Tee	24 x 15/16 x 1-11/16"	–	74.38	–
<b>Molding</b>						
7/8"	<b>HD7801G90</b> _ _	10' Hemmed Angle Molding	120 x 7/8 x 7/8"	–	–	–
<b>Accessories</b>						
2"	<b>BACG90A</b>	Wind Uplift Clip	N/A	–	–	–
	<b>UHDC</b>	Universal Hold-down Clip	N/A	–	–	–

\* Simple Span

♦ Add 2-letter color suffix to item number when specifying or ordering. Available in White Steel and Tech Black (ex. HD7801G90A **BL**)

#### PERFORMANCE

Fire Guard	Seismic Category
Dots represent high level of performance.	
•	•
•	•
•	•

#### PACKAGING

Pcs./ Ctn.	LFT/ Ctn.
20	240
60	240
60	120
30	300
20	240
60	240
60	120
30	300
250	–
1000	–

ASTM Class  
 HD - Heavy-duty  
 ID - Intermediate-duty  
 LD - Light-duty


#### DETAILS For more information on Prelude Plus XL Fire Guard, see submittal BPCS-3156.



PRELUDE XL Main Beam



PRELUDE XL Cross Tee



TechLine / 1 877 276-7876  
[armstrongceilings.com/commceilings](http://armstrongceilings.com/commceilings)  
 (search: suspensionsystems)

BPCS-3156-718

LEED® is a registered trademark of the U.S. Green Building Council  
 All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2018 AWI Licensing LLC  
 Printed in the United States of America

