

TECTUM®

Lay-in
coarse texture



Tectum® Lay-in 24" x 24" panels in White with Prelude® XL® 15/16" suspension system (Pgs. 458-459)

plus capabilities
to do more

armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Tectum® Lay-in ceiling panels provide durable, sustainable, acoustical options for a wide variety of applications.

KEY SELECTION ATTRIBUTES



- Tectum® panels are Living Product Imperative Certified by the International Living Future Institute – 1" panels in White and Natural only
- Tectum panels are part of the Sustain® portfolio and meet the most stringent sustainability standards today – 1" panels in White and Natural only
- Durable for heavy use interiors
- Wide variety of color options available, including custom colors
- Can be field painted up to six times without impacting acoustic or fire performance
- Short lead times

TYPICAL APPLICATIONS


- Gymnasiums
- Auditoriums
- Multi-purpose Spaces
- Exposed Structures
- Acoustical Retrofits
- Education Spaces

COLORS Due to printing limitations, shade may vary from actual product.




LINE DESIGN CAPABILITIES

Available through special order.



DETAILS



1. Tectum® Lay-in
2. Tectum® Lay-in with Prelude® 15/16" suspension system

Note: Panel edges are unfinished.

TECTUM®

Lay-in coarse texture



Declare™
Third Party Verified
Living Product
Imperative
Certified



For LEED contribution visit
armstrongceilings.com/greengenie



VISUAL SELECTION

Edge Profile	Suspension Detail Dwg. Pgs. 474-478	Item No. ◆	Dimensions (Inches)
TECTUM® Lay-in (FSC® Certified)			
15/16" Square Lay-in	1	8184T10 __	24 x 24 x 1" □
	1	8183T10 __	24 x 48 x 1" □
	1	Other Size Panels	1", 1-1/2", or 2" thickness

PERFORMANCE SELECTION

Dots represent high level of performance.

LOCATION DEPENDENT

Fire Rating	Light Reflect (White Only)	Mold & Mildew Protection BioBlock	Sag Resist Humi-Guard+	Certified Low VOC Emissions	Wash	Impact	Scratch	30-Yr Warranty
Class A	Up to 0.75	•	•	•	•	•	•	•
Class A	Up to 0.75	•	•	•	•	•	•	•
Class A	Up to 0.75	•	•	–	•	•	•	•


ACOUSTICAL INFORMATION

Item No.	Infill Panel Item No.	NRC	+ CAC	=	Total Acoustics ¹
8184T10 __	–	0.40	–	–	–
8183T10 __	–	0.40	–	–	–
8184T10 __	1713	0.90	33	–	–
8183T10 __	1713	0.90	33	–	–

¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.
GOOD (NRC 0.60-0.65; CAC 35+)
BETTER (NRC 0.70-0.75; CAC 35+)
BEST (NRC 0.80+; CAC 35+)

◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural, TWH = White (e.g. 8184T10 I W H)
 For special sizes, and colors, call TechLine at 1 877 276-7876.

ACCESSORIES




Tectum® Hold-Down Clip
8178T10 – 1" Panel Thickness
8178T20 – 1-1/2" Panel Thickness

Attaches to main beams and cross tees behind lay-in ceilings; helps prevent panel displacement from non-deliberate contact by basketballs and other forces from below the ceiling.

1713	School Zone™ Fine Fissured Lay-in Acoustical Panel	24 x 24 x 3/4"	White	12 pcs/ctn
-------------	---	----------------	-------	------------

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
 Cementitious Wood Fiber; FSC®-certified (COC-003601). For more information about FSC®-certified fire-retardant products, or to view our FSC®-certification letter, contact TechLine at 1 877 276 7876.

Surface Finish
 Factory-applied latex paint with Silicate surface coating for abuse resistance. Natural is unpainted.

Fire Performance
 Class A per IBC. Flame Spread Index 25 or less and Smoke Developed Index 50 or less when tested in accordance with ASTM E84.

CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less and Smoke Developed Index of 50 or less.

VOC Emissions
 Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED®, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Humidity/Sag Resistance
 HumiGuard® Plus panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection
 Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

Installation Considerations
 Use caution and wear appropriate hand, eye, and dust mask protection when cutting and installing Tectum® panels. Refer to installation instructions for complete details and cutting recommendations.

Primary (Embodied) Energy
 See all LCA information on our EPD's.

Application Considerations
 Color variation among panels is common due to the natural characteristics of the wood on White and Natural panels.

Wood fibers may appear orange on Natural colored panels due to the characteristics of the wood.

Design Support
 Project management assistance is available by calling TechLine at 1 877 276 7876.

Specification Consideration
FSC Certified panels available upon request.

Attention: For FSC®-certified wood products to maintain their CoC certification, products must be sold to a CoC-certified distributor or directly to the installing contractor. Failure to do so breaks the CoC.

Seismic Restraint
 Tectum® Lay-in panels are approved for application in all seismic areas when installed per Armstrong Ceilings Installation Instructions.

Warranty
 30-Year Performance Guarantee and Warranty when installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
 1" – 1.65 lbs/SF
 8183T10 – 4 pcs/ctn
 8184T10 – 8 pcs/ctn

TechLine / 1 877 276-7876
 armstrongceilings.com/TECTUM

BPCS-5615-918

LEED® is a registered trademark of the U.S. Green Building Council®.
 Declare™ is a service mark of The International Living Future Institute.
 FSC® is a registered trademark of FSC Forest Stewardship Council®, A.C., license code FSC-C007626. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates. © 2018 AWI Licensing LLC
 Printed in the United States of America



395

TECTUM® WOOD FIBER – CEMENTITIOUS