FINE FISSURED™
FINE FISSURED™ High NRC

Tegular
medium texture

TOTAL ACOUSTICS®
Sound Absorption (NRC)
+ Sound Blocking (CAC)

Fine Fissured

Fine Fissured™ High NRC

Fine Fissured™ Tegular panels with Prelude® XL® suspension system (Pgs. 458-459)

See more photos at:
armstrongceilings.com/photogallery
SEARCH: fine fissured

This economical, non-directional panel available in standard and high acoustical absorption options.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance™
- Options provide excellent combination of acoustical performance NRC up to 0.75, CAC up to 35, and Articulation Class 170
- Fine Fissured™ School Zone® items help comply with ANSI S12.60 Classroom Guidelines
- Non-directional visual reduces scrap and installation time
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- 10-Year replacement panel available for itesm 1732,1734

10-YEAR REPLACEMENT PANEL AVAILABILITY

COLORS Due to printing limitations, shade may vary from actual product.

White (WH) | Ivory (IV) | Medium Taupe (MT) | Light Grey (LG) | Grey Stone (GS) | Adobe (AD) | Tech Black (BL)

Item 1732 is available in colors.
All other items are available in White only.
Colored ceilings are dye-lotted and should be segregated by dye lot. Do not mix.

DETAILS (Other Suspension Systems compatible. Refer to listing on page 317.)

1. Fine Fissured™ Beveled Tegular
2. Fine Fissured™ Angled Tegular
3. Fine Fissured™ Tegular with Suprafine® 9/16" suspension system

FINE FISSURED™
FINE FISSURED™ High NRC

Tegular
medium texture

GREENGUARD Gold Certified (details below)

UP TO 73% RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®: energy management; construction waste mgmt; regional materials; design for flexibility; EPD; recyclable/ extended producer resp.; biobased materials; recycled content; sourcing of raw materials; material ingredient reporting; low emitting/ materials; lighting quality; acoustics

LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION
Dots represent high level of performance. $$$$

Edge Profile	Susp. Dwg. Pgs. 474-478 armstrongceilings.com/catdwgs	Item No. ◆	Dimensions (Inches)	UL Classified Acoustics NRC	UL Classified Acoustics CAC	Total Acoustics[1] NRC+CAC	Articulation Class AC	Fire Performance	Light Reflect	Mold & Mildew Protection Bio-Block	Sag Resist Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
FINE FISSURED™ High NRC																
15/16" Angled Tegular	13	**1756**	24 x 24 x 7/8" □	0.75 •	35 •	BETTER	170 •	Class A	0.85 •	•	•	•	Std	•	•	•
	13	**1757**	24 x 48 x 7/8" ▭	0.75 •	35 •	BETTER	170 •	Class A	0.85 •	•	•	•	Std	•	•	•
9/16" Beveled Tegular	29, 44, 48, 52, 56	**1758**	24 x 24 x 7/8" □	0.75 •	35 •	BETTER	170 •	Class A	0.85 •	•	•	•	Std	•	•	•
	29, 44, 48, 52, 56	**1759**	24 x 48 x 7/8" ▭	0.75 •	35 •	BETTER	170 •	Class A	0.85 •	•	•	•	Std	•	•	•
FINE FISSURED™																
15/16" Angled Tegular	12	**1732_ _**	24 x 24 x 5/8" □	0.55	35 •	–	–	Class A	0.82* •	•	•	•	Std	•	•	•
	12	**1833**	24 x 24 x 5/8" □	0.55	35 •	–	–	Fire Guard™	0.82 •	•	•	•	Std	Std	•	•
	12	**1733**	24 x 48 x 5/8" ▭	0.55	35 •	–	–	Class A	0.82 •	•	•	•	Std	Std	•	•

MORE ITEMS ▶

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound-blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)
◆ Add 2-letter color suffix to item number when specifying or ordering (e.g., 1732 | V)
* Light reflectance number for white panels only

SUSPENSION SYSTEMS

15/16"
- Prelude® XL® / Prelude® XL® Fire Guard™

9/16"
- Silhouette® 1/4" Reveal
- Silhouette 1/8" Reveal
- Suprafine® / Suprafine® XL® Fire Guard
- Interlude®
- Sonata®

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies. (Class A).

ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

VOC Emissions
GREENGUARD Gold Certified
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED, WELL, Living Building Challenge, CalGreen Title 24, ANSI/ ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® XL® suspension system for 15/16" edge detail and Silhouette suspension system for 9/16" edge detail.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
1732 – 0.70 lbs/SF; 64 SF/ctn
1733 – 0.70 lbs/SF; 80 SF/ctn
1833 – 1.05 lbs/SF; 48 SF/ctn
1756, 1758 – 1.08 lbs/SF; 40 SF/ctn
1757, 1759 – 1.08 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
1732M, 1733M, 1756M, 1757M, 1758M, 1759M – Metric items subject to extended lead times and minimum quantities.

FINE FISSURED™
FINE FISSURED™ High NRC

Tegular
medium texture

GREENGUARD Gold Certified (details below)

UP TO 56% RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED® ✓ energy management ✓ construction waste mgmt ✓ regional materials ✓ design for flexibility ✓ EPD ✓ recyclable/ extended producer resp. ✓ biobased materials ✓ recycled content ✓ sourcing of raw materials ✓ material ingredient reporting ✓ low emitting/ materials ✓ lighting quality ✓ acoustics

▲ LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance. $$$$

Edge Profile	Susp. Dwg. Pgs. 474-478 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	UL Classified Acoustics NRC	+ CAC	= Total Acoustics[1] NRC + CAC	Articulation Class	Fire Performance	Light Reflect	Mold & Mildew Protection Bio-Block	Sag Resist Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
FINE FISSURED™																
15/16" Angled Tegular	12	**1834**	24 x 48 x 5/8"	0.55	35 •	–	N/A	Fire Guard™	0.82 •	•	•	•	Std	•	•	•
9/16" Beveled Tegular	29, 44, 48, 52, 56	**1734**	24 x 24 x 5/8"	0.55	35 •	–	N/A	Class A	0.82 •	•	•	•	Std	Std	•	•
	29, 44, 48, 52, 56	**1835**	24 x 24 x 5/8"	0.55	35 •	–	N/A	Fire Guard	0.82 •	•	•	•	Std	Std	•	•
FINE FISSURED™ Size Capabilities		Made-to-Order Sizes (4-6 Wks)	Width 5/8" Thick: 12" - 30" / Length: 18" - 72"	–	–	–	N/A	Fire Guard	0.82 •	•	•	•	Std	Std	•	•
15/16" Angled Tegular 9/16" Beveled Tegular																
School Zone® FINE FISSURED																
15/16" Angled Tegular	13	**1717**	24 x 24 x 3/4"	0.70 •	40 •	BETTER	N/A	Class A	0.85 •	•	•	•	Std	•	•	•
	13	**1820**	24 x 24 x 3/4"	0.70 •	35	BETTER	N/A	Fire Guard	0.85 •	•	•	•	Std	•	•	•
	13	**1824**	24 x 48 x 3/4"	0.70 •	35	BETTER	N/A	Fire Guard	0.85 •	•	•	•	Std	•	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound-blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

FINE FISSURED™
FINE FISSURED™ High NRC

Tegular
medium texture

GREENGUARD Gold Certified
(details below)

UP TO 56% RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®: energy management; construction waste mgmt; regional materials; design for flexibility; EPD; recyclable/ extended producer resp.; biobased materials; recycled content; sourcing of raw materials; material ingredient reporting; low emitting/ materials; lighting quality; acoustics

▲ LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance. $$$$

Edge Profile	Susp. Dwg. Pgs. 474-478 armstrongceilings.com/catdwgs	Item No. ◆	Dimensions (Inches)		UL Classified Acoustics NRC	+ CAC	= NRC+CAC	Total Acoustics[1]	Articulation Class	Fire Performance	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
												Bio-Block	Humi-Guard+					
School Zone® FINE FISSURED™																		
9/16" Beveled Tegular	29, 44, 48, 52, 56	**1719**	24 x 24 x 3/4"	☐	0.70 •	40 •		BETTER	N/A	Class A	0.85 •	•	•	•	Std	•	•	•
	29, 44, 48, 52, 56	**1821**	24 x 24 x 3/4"	☐	0.70 •	35 •		BETTER	N/A	Fire Guard™	0.85 •	•	•	•	Std	•	•	•
School Zone® FINE FISSURED™ Size Capabilities			**Width**	**Length**														
15/16" Angled Tegular 9/16" Beveled Tegular		Made-to-Order Sizes (4-6 Wks)	**3/4" Thick** 12" - 30"	18" - 72"	–	–		–	N/A	Class A	0.85 •	•	•	•	Std	Std	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound-blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

15/16"

Prelude® XL®
Prelude® XL® Fire Guard™

9/16"



Silhouette® 1/4" Reveal



Silhouette 1/8" Reveal



Suprafine®
Suprafine® XL® Fire Guard™



Interlude®



Sonata®

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

VOC Emissions
GREENGUARD Gold Certified
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED, WELL, Living Building Challenge, CalGreen Title 24, ANSI/ ASHRAE/USGBC/ IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® XL® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
1820, 1821 – 1.31 lbs/SF; 48 SF/ctn
1717, 1719 – 1.25 lbs/SF; 48 SF/ctn
1834 – 1.05 lbs/SF; 64 SF/ctn
1734 – 0.70 lbs/SF; 64 SF/ctn
1835 – 1.05 lbs/SF; 48 SF/ctn
1824 – 1.20 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
1820M, 1821M, 1717M, 1719M, 1834M, 1734M, 1824M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

LEED® is a registered trademark of the U.S. Green Building Council
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2019 AWI Licensing LLC Printed in the United States of America