

# FINE FISSURED™

Tile  
medium texture



Fine Fissured™ tile with Prelude® Concealed 15/16" suspension system (Pg. 454)

Fine Fissured™ panels offer a non-directional visual, standard acoustics, and concealed or tongue-and-groove installation.

## KEY SELECTION ATTRIBUTES

- 12" x 12" concealed tile option provides grid-hiding monolithic installation
- Non-directional visual reduces scrap and installation time
- 30-Year Limited System Warranty against visible sag, mold and mildew

## COLORS



White  
(WH)

# FINE FISSURED™

Tile  
medium texture

**GREENGUARD**  
Gold Certified  
(details below)



**56% RECYCLED CONTENT**

LEED®

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

## VISUAL SELECTION

| Edge Profile  | Susp. Dwg. Pgs. 474-478<br><a href="http://armstrongceilings.com/catdwgs">armstrongceilings.com/catdwgs</a> | Item No.   | Dimensions (Inches) |
|---|---|------------|---------------------|
| <b>FINE FISSURED™ Tile</b>  |   |            |                     |
| Concealed   | 66  | <b>746</b> | 12 x 12 x 5/8" □    |
|  |   |            |                     |
| Tongue-and-Groove   | 63  | <b>741</b> | 12 x 12 x 1/2" □    |
|  |   |            |                     |

## PERFORMANCE SELECTION


Dots represent high level of performance.

| UL Classified Acoustics |       | Total Acoustics <sup>1</sup> | Fire Performance | Light Reflect | Mold & Mildew Protection | Sag Resist  | Certified Low VOC Emissions | Durability | Recycled Content | Recycle Program | Warranty |
|-------------------------|-------|------------------------------|------------------|---------------|--------------------------|-------------|-----------------------------|------------|------------------|-----------------|----------|
| NRC                     | + CAC | =                            |                  | Light Reflect | Bio-Block                | Humi-Guard+ |                             |            |                  |                 |          |
| 0.55                    | 35    | -                            | Class A          | 0.82          | •                        | •           | •                           | Std        | •                | •               | 30-Yr    |
| 0.55                    | N/A   | -                            | Class A          | 0.82          | •                        | •           | •                           | Std        | •                | •               | 30-Yr    |

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product. Splines not included in carton. Not recyclable when glue-up installation method is used.

## SUSPENSION SYSTEM

15/16" Concealed



Prelude® Concealed or Adhesive

## STAPLE UP/ADHESIVE

Tongue-and-Groove



## PHYSICAL DATA

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied latex paint

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled.)

### ASTM E1264 Classification

Type III, Form 2, Pattern C E  
Fire Class A

### Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

### Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

### VOC Emissions

**GREENGUARD Gold Certified**

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
[UL.COM/GG](http://UL.COM/GG)  
UL 2818



### Insulation Value

R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

### 30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at [armstrongceilings.com](http://armstrongceilings.com)

### Weight; Square Feet/Carton

741 – 0.75 lbs/SF; 40 SF/ctn  
746 – 0.90 lbs/SF; 40 SF/ctn

### Minimum Order Quantity

1 carton