



Calla® Ceiling Panels
Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA; Pensacola, Florida, USA

Life Expectancy: 30 Years

Embodied Carbon: 0.816 kg CO₂-eq ▼

Declared Unit: 1 ft²

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program)

Ingredients:

Mineral Wool; Perlite; Starch; Recycled Paper; Clay; Aluminum Trihydrate; Salt of Polycarboxylic Acid; Limestone; PVA; Titanium Dioxide; Calcium Carbonate; Proprietary Ingredient (<1%); Poly (Vinyl Alcohol); Plasticizer; Starch; Diatomaceous Earth; Amorphous Silica; Silica; Hydroxyethylcellulose; Mica; Quartz; Poly Hydroxy

¹LBC Temp Exception I10-E4 Proprietary Ingredients <1%

Living Building Challenge Criteria: Compliant

LBC Red List Free Red List Approved Declared

I-10 Interior Performance: CDPH Standard Method v1.1-2010

ARM-0001
EXP. 01 OCT 2020
Original Issue Date: 2016

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare