

TECTUM®
Tegular
coarse texture



plus capabilities
to do more

armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Tectum® Tegular ceiling panels provide durable, sustainable, acoustical options for a wide variety of applications.

KEY SELECTION ATTRIBUTES




- Tectum® panels are Living Product Imperative Certified by the International Living Future Institute – 1" panels in White and Natural only
- Get Total Noise Control and design flexibility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance™
- Tectum panels are part of the Sustain® portfolio and meet the most stringent sustainability standards today – 1" panels in White and Natural only
- USDA Certified Biobased Product, 98%
- Durable for heavy use interiors
- Wide variety of color options available, including custom colors
- Short lead times
- Can be field painted up to six times without impacting acoustic or fire performance

TYPICAL APPLICATIONS


- Gymsnasiums
- Auditoriums
- Multi-purpose Spaces
- Corridors
- Education Spaces

COLORS Due to printing limitations, shade may vary from actual product.



LINE DESIGN CAPABILITIES

Available through special order.



DETAILS



1. Tectum® Tegular
 2. Tectum® Tegular with Prelude® 15/16" suspension system
- Note: Panel edges including visible Tegular edge are unfinished.

TECTUM®

Tegular

coarse texture



Declare®
Third Party Verified
Living Product
Imperative
Certified



SUSTAIN®
High Performance
Sustainable
Ceiling Systems



The mark of
responsible forestry

For LEED contribution visit
armstrongceilings.com/greengenie



VISUAL SELECTION

Edge Profile	Suspension Detail Dwg. Pgs. 474-478	Item No. ◆	Dimensions (Inches)
TECTUM® Tegular (FSC® Certified)			
15/16" Square Tegular	8	8186T10 __	24 x 24 x 1" □
	8	8185T10 __	24 x 48 x 1" □
	8	Other Size Panels	1", 1-1/2", or 2" thickness

◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural, TWH = White (e.g. 8185T10 I W H)
For special sizes, and colors, call TechLine at 1 877 276-7876.

PERFORMANCE SELECTION

Dots represent high level of performance.

LOCATION DEPENDENT

Fire Rating	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Impact	Scratch	30-Yr Warranty
Class A	Up to 0.75	•	•	•	•	•	•
Class A	Up to 0.75	•	•	•	•	•	•
Class A	Up to 0.75	•	•	•	•	•	•

ACOUSTICAL INFORMATION


Item No.	Infill Panel Item No.	NR C	CAC	Total Acoustics ¹
8186T10 __	-	0.40	-	-
8185T10 __	-	0.40	-	-
8186T10 __	1713	0.90	35	BEST
8185T10 __	1713	0.90	35	BEST

¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.
GOOD (NRC 0.60-0.65; CAC 35+)
BETTER (NRC 0.70-0.75; CAC 35+)
BEST (NRC 0.80+; CAC 35+)

ACOUSTICAL INFILL PANELS

1713	School Zone® Fine Fissured Lay-in Acoustical Panel	24 x 24 x 3/4"	White	12 pcs/ctn
-------------	--	----------------	-------	------------

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Cementitious Wood Fiber; FSC®-certified (COC-003601). For more information about FSC®-certified fire-retardant products, or to view our FSC®-certification letter, contact TechLine at 1 877 276 7876.

Surface Finish
Factory-applied latex paint with Silicate surface coating for abuse resistance. Natural is unpainted.

Fire Performance
Class A per IBC. Flame Spread Index 25 or less and Smoke Developed Index 50 or less when tested in accordance with ASTM E84.
CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less and Smoke Developed Index of 50 or less (painted, face only).

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED®, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Humidity/Sag Resistance
HumiGuard® Plus panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

Installation Considerations
Use caution and wear appropriate hand, eye, and dust mask protection when cutting and installing Tectum® panels. Refer to installation instructions for complete details and cutting recommendations.

Primary (Embodied) Energy
See all LCA information on our EPDs.

Application Considerations
Color variation among panels is common due to the natural characteristics of the wood on White and Natural panels. Wood fibers may appear orange on Natural colored panels due to the characteristics of the wood.

Specification Consideration
FSC Certified panels available upon request.
Attention: For FSC®-certified wood products to maintain their CoC certification, products must be sold to a CoC-certified distributor or directly to the installing contractor. Failure to do so breaks the CoC.

Seismic Restraint
Tectum Tegular panels are approved for application in all seismic areas when installed per Armstrong Ceilings Installation Instructions.

Warranty
30-Year Performance Guarantee & Warranty when installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
1" – 1.65 lbs/SF
8186T10 – 8 pcs/ctn
8185T10 – 4 pcs/ctn

TechLine / 1 877 276-7876
armstrongceilings.com/TECTUM

BPCS-5616-920

LEED® is a trademark of the U.S. Green Building Council®
Declare® is a trademark of The International Living Future Institute
FSC® is a trademark of FSC Forest Stewardship Council®, A.C., license code FSC-C007626. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates. © 2020 AWI Licensing LLC
Printed in the United States of America



397



TECTUM® WOOD FIBER – CEMENTITIOUS