

TECTUM® Finale™
Acoustical Wall Panels
coarse texture



LEED® WELL™ | LBC

energy management	construction waste mgmt	regional materials	design for flexibility	EPD	recyclable/extended producer resp.	biobased materials	FSC® (for wood)	recycled content	sourcing of raw materials	material ingredient reporting	low emitting materials	lighting quality	acoustics

LOCATION DEPENDENT

For LEED contribution visit armstrongceilings.com/greengenie



Tectum® Finale™ high NRC walls provide durable, sustainable, acoustical solutions for a wide variety of applications.

KEY SELECTION ATTRIBUTES

- new** 1" thick Tectum® Finale™ wall panels with 1" factory-attached furring are now available as standard items.
- Finale panels now sold by the piece – get the quantity you need without extra material
- Built-in furring pieces with factory-filled panels provide maximum sound control and install 2.5x faster than Direct-Attach for the same acoustic performance
- Excellent sound absorption – 1" panels have NRC up to 0.95 (mounting method dependent)
- Panel sizes include 24" x 48", 24" x 96", 48" x 48", and 48" x 96", with bevel on long edges, square on short sides. Custom panels are available in additional sizes and thicknesses upon request (ASQuote@armstrongceilings.com)
- new** CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (standard colors only)
- Abuse resistant for active spaces
- Can be mechanically fastened to a wide variety of surfaces including masonry, drywall, wood, and more

COLORS Due to printing limitations, shade may vary from actual product.

FAST
3 WEEKS
order to ship

Standard Colors



White (TWH)



Natural (TNA)



Custom Colors Available

▲ Tectum® Finale™ Wall Panels (also available for ceiling applications)

VISUAL SELECTION

Item No. ◆	Dimensions W x L x D (Inches)	
TECTUM® Finale™ Wall Panels	8215W2L04T10_ _ _ 24 x 48 x 1"	
	8215W4L04T10_ _ _ 48 x 48 x 1"	
	8215W2L08T10_ _ _ 24 x 96 x 1"	
	8215W4L08T10_ _ _ 48 x 96 x 1"	
	8215W1L01T10_ _ _ 12 x 12 x 1"	

FAST
3 WEEKS
order to ship

Made-to-order items ready to ship from manufacturer to shipping location in 3 weeks or less. For more information visit armstrongceilings.com/fast134.

PERFORMANCE Dots represent high level of performance.

Fire Rating	Light Reflect	Anti-Mold/Mildew	Sag Resist	Fog	Impact	Scratch	30-Yr Warranty	DURABILITY	
								CleanAssure™ Disinfectable Panels	
Class A	Up to 0.75	•	•	•	•	•	•	•	•
Class A	Up to 0.75	•	•	•	•	•	•	•	•
Class A	Up to 0.75	•	•	•	•	•	•	•	•
Class A	Up to 0.75	•	•	•	•	•	•	•	•
Class A	Up to 0.75	•	•	•	•	•	•	•	•

ACOUSTICAL INFORMATION

Total Panel Thickness	NRC	Mounting Method
1" with integral Minwool insert & 1" furring	0.85 • 0.95 •	A D-20
1-1/2" with integral Minwool insert & 1" furring	N/A N/A	A D-20
2" with integral Minwool insert & 1" furring	N/A N/A	A D-20

◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural (unpainted), TWH = White (e.g. 8215W2L04T10 I W H)
Four-sided beveled edge panels are recommended in adjoining panel installations
For special sizes, and colors, call TechLine at 1 877 276-7876.

ACCESSORIES, PANEL CONSTRUCTION DETAIL & EDGE DETAIL RECOMMENDATIONS (Tectum® Finale Ceiling panels, armstrongceilings.com/tectumfinalewalls)

PHYSICAL DATA (Tectum® Finale Ceiling panels, armstrongceilings.com/tectumfinalewalls)

