

CIRRUS® High NRC  
CIRRUS® High CAC & CIRRUS®

Tegular  
medium texture




CONTAIN CLEAN PROTECT



CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



**DESIGNFlex®**  
A New World of Choice  
for Ceiling Systems



▲ Cirrus® Beveled Tegular panels with Suprafine® XL® 9/16" suspension system

See more photos at:  
[armstrongceilings.com/photogallery](http://armstrongceilings.com/photogallery)  
SEARCH: cirrus

Medium-texture panels offer both Sustain® and Total Acoustics® panel performance; Good noise reduction and sound blocking in one panel.

KEY SELECTION ATTRIBUTES

- DESIGNFlex® options include made-to-order sizes available to ship in 3 weeks
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent sustainability compliance standards today
- **new** CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- **new** New colors to complement interiors
- Excellent combination of acoustical performance: NRC up to 0.75 and CAC 35
- High NRC items feature Articulation Class 170 helpful to control sound over wall partitions
- Ceiling-2-Ceiling™ post-consumer recycled content options. Items 589HRC, 539HRC, 584HRC, 535HRC. 71% pre-consumer; 15% post-consumer
- Mold- and mildew-resistant surface
- USDA-Certified Biobased Product – 91%
- 10-Year replacement panel available for items 584, 589



COLORS Due to printing limitations, shade may vary from actual product.



DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Cirrus® Angled Tegular
2. Cirrus® Beveled Tegular
3. Cirrus® Angled Tegular with Prelude® XL® 15/16" suspension system
4. Cirrus® Beveled Tegular with Suprafine® XL® 9/16" suspension system

# CIRRUS® High NRC

Tegular  
medium texture

USDA  
CERTIFIED  
BIOBASED  
PRODUCT  
PRODUCT 91%

**SUSTAIN\***  
High Performance  
Sustainable Ceiling Systems

Declare.

**GREENGUARD**  
Gold Certified  
(details below)

LEED®  
WELL™ | LBC

UP TO **73%** RECYCLED  
CONTENT

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT

## VISUAL SELECTION

| armstrongceilings.com/catdwgs                 | Susp. Dwg.               | Item No. | Dimensions (Inches)  |
|---|--------------------------|----------|--|
| CIRRUS® High NRC<br>15/16"<br>Angled Tegular  | 13                       | 556      | 24 x 24 x 7/8"   |
|   |                          | 551      | 24 x 48 x 7/8"   |
| 9/16"<br>Beveled Tegular                      | 29, 44,<br>48, 52,<br>56 | 558      | 24 x 24 x 7/8"   |
|   |                          | 568      | 24 x 48 x 7/8"   |
| Made-to-Order<br>Sizes<br>CIRRUS®<br>High NRC |                          |          | 7/8" Thick – 15/16" Angled Tegular & 9/16" Beveled Tegular |
|   |                          |          | Width      Length  |
|   |                          |          | 4" - 24"      4" - 48"                                     |

**3-4**  
WEEKS  
order to ship

## PERFORMANCE SELECTION


Dots represent high level of performance.

| UL Classified Acoustics | Total Acoustics <sup>1</sup> | Articulation Class | Fire Performance | Light Reflect | Anti-Mold/Mildew | Sag Resistant | Certified Low VOC Emissions | CleanAssure™ Disinfectable Panels | Durability | Recycle Program | 30-Yr Warranty |
|-------------------------|------------------------------|--------------------|------------------|---------------|------------------|---------------|-----------------------------|-----------------------------------|------------|-----------------|----------------|
| 0.75<br>•               | 35<br>•                      | BETTER<br>( )))    | 170<br>•         | Class A       | 0.85<br>•        | •             | •                           | •                                 | Std        | •               | •              |
| 0.75<br>•               | 35<br>•                      | BETTER<br>( )))    | 170<br>•         | Class A       | 0.85<br>•        | •             | •                           | •                                 | Std        | •               | 10-Yr          |
| 0.75<br>•               | 35<br>•                      | BETTER<br>( )))    | 170<br>•         | Class A       | 0.85<br>•        | •             | •                           | •                                 | Std        | •               | •              |
| 0.75<br>•               | 35<br>•                      | BETTER<br>( )))    | 170<br>•         | Class A       | 0.85<br>•        | •             | •                           | •                                 | Std        | •               | 10-Yr          |
| N/A                     | N/A                          | N/A                | N/A              | Class A       | 0.85<br>•        | •             | •                           | •                                 | Std        | •               | 10-Yr          |

**MORE ITEMS** ▶

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

**ASTM E1264 Classification**  
Type III, Form 1, Pattern E I  
Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
**GREENGUARD Gold Certified**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustic Performance**  
CAC testing conducted using Silhouette® suspension system.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS  
UL.COM/GG  
UL 2818



**Insulation Value**  
R Factor – 1.9 (BTU units)  
R Factor – 0.33 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
551 – 1.21 lbs/SF; 48 SF/ctn  
556, 558 – 1.50 lbs/SF; 40 SF/ctn  
568 – 1.25 lbs/SF; 48 SF/ctn

**Metric Items Available**  
551M, 558M, 568M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



CIRRUS®  
Tegular  
medium texture



USDA  
CERTIFIED  
BIOBASED  
PRODUCT  
PRODUCT 91%

Declare.

SUSTAIN®  
High Performance  
Sustainable Ceiling Systems  
GREENGUARD  
Gold Certified  
(details below)

LEED® WELL™ LBC  
UP TO 77% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$

| armstrongceilings.com/catdws        | Susp. Dwg.         | Item No. | Dimensions (Inches) | UL Classified Acoustics | Total Acoustics <sup>1</sup> | Articulation Class | Fire Performance | Light Reflect | Anti-Mold/Mildew | Sag Resistant | Certified Low VOC Emissions | Fog | Durability | Recycle Program | 30-Yr Warranty |
|-------------------------------------|--------------------|----------|---------------------|-------------------------|------------------------------|--------------------|------------------|---------------|------------------|---------------|-----------------------------|-----|------------|-----------------|----------------|
| CIRRUS®<br>9/16"<br>Beveled Tegular | 29, 44, 48, 52, 56 | 589_**   | 24 x 24 x 3/4"      | 0.70                    | 35                           | BETTER             | N/A              | Class A       | 0.85*            | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 589HRC   | 24 x 24 x 3/4"      | .                       | .                            | ( )))              |                  |               |                  |               |                             |     |            |                 |                |
|                                     |                    | 538      | 24 x 24 x 7/8"      | 0.70                    | 38                           | BETTER             | N/A              | Class A       | 0.85             | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 577      | 24 x 24 x 3/4"      | 0.35                    | 35                           | N/A                | N/A              | Fire Guard™   | 0.85             | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 539_**   | 24 x 48 x 3/4"      | 0.70                    | 35                           | BETTER             | N/A              | Class A       | 0.85*            | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 539HRC   | 24 x 48 x 3/4"      | .                       | .                            | ( )))              |                  |               |                  |               |                             |     |            |                 |                |
| 15/16"<br>Angled Tegular            | 13                 | 584_**   | 24 x 24 x 3/4"      | 0.70                    | 35                           | BETTER             | N/A              | Class A       | 0.85*            | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 584HRC   | 24 x 24 x 3/4"      | .                       | .                            | ( )))              |                  |               |                  |               |                             |     |            |                 |                |
|                                     |                    | 578      | 24 x 24 x 3/4"      | 0.35                    | 35                           | N/A                | N/A              | Fire Guard    | 0.85             | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 534      | 24 x 24 x 7/8"      | 0.70                    | 38                           | BETTER             | N/A              | Class A       | 0.85             | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 535_**   | 24 x 48 x 3/4"      | 0.70                    | 35                           | BETTER             | N/A              | Class A       | 0.85*            | .             | .                           | .   | Std        | .               | .              |
|                                     |                    | 535HRC   | 24 x 48 x 3/4"      | .                       | .                            | ( )))              |                  |               |                  |               |                             |     |            |                 |                |

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)  
\* White only  
\*\* Add 2-letter color suffix to item number when specifying or ordering (e.g., 839 LG).

PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).  
Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A)

**ASTM E1264 Classification**  
Type III, Form 1, Pattern E I; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Design Considerations**  
Color ceilings are dye-lotted and should be segregated by dye lot. Do not mix. Coordinating suspension system colors are available.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/ES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustic Performance**  
CAC testing conducted using Silhouette® suspension system.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS  
UL.COM/GG  
UL 2818



**Insulation Value**  
R Factor – 1.9 (BTU units)  
R Factor – 0.33 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
534, 538 – 1.38 lbs/SF; 40 SF/ctn  
535, 535HRC, 539, 539HRC – 1.21 lbs/SF; 48 SF/ctn  
577, 578 – 1.25 lbs/SF; 48 SF/ctn  
584, 584HRC, 589, 589HRC – 1.06 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
1 carton

**Metric Items Available**  
584M, 578M, 534M, 572M, 581M, 535M, 589M, 538M, 577M, 583M, 539M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine 877 276-7876  
armstrongceilings.com/cirrus

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are trademarks of the International Living Future Institute®; WELL™ and Well Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are registered trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2021 AWI Licensing LLC



MINERAL FIBER – Standard

# CIRRUS® High CAC

Tegular  
medium texture

USDA  
CERTIFIED  
BIOBASED  
PRODUCT  
PRODUCT 91%

SUSTAIN®  
High Performance  
Sustainable Ceiling Systems

Declare.

GREENGUARD  
Gold Certified  
(details below)

LEED®  
WELL™ | LBC

UP TO 73% RECYCLED  
CONTENT

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

## VISUAL SELECTION

| armstrongceilings.com/catdwgs             | Susp. Dwg.         | Item No. | Dimensions (Inches) |
|---|--------------------|----------|---------------------|
| CIRRUS® High CAC<br>15/16" Angled Tegular | 13                 | 572      | 24 x 24 x 7/8"      |
|   |                    | 581      | 24 x 48 x 7/8"      |
| 9/16" Beveled Tegular                     | 29, 44, 48, 52, 56 | 576      | 24 x 24 x 7/8"      |
|   |                    | 583      | 24 x 48 x 7/8"      |

## PERFORMANCE SELECTION

Dots represent high level of performance.

| UL Classified Acoustics | Total Acoustics <sup>1</sup> | Articulation Class | Fire Performance | Light Reflect | Anti-Mold/Mildew | Sag Resistant | Certified Low VOC Emissions | CleanAssure™ Disinfectable Panels | Durability | Recycle Program | 30-Yr Warranty |
|-------------------------|------------------------------|--------------------|------------------|---------------|------------------|---------------|-----------------------------|-----------------------------------|------------|-----------------|----------------|
| 0.70<br>•               | 40<br>•                      | BETTER<br>( )))    | N/A              | Class A<br>•  | 0.85<br>•        | •             | •                           | •                                 | Std        | •               | •              |
| 0.70<br>•               | 40<br>•                      | BETTER<br>( )))    | N/A              | Class A<br>•  | 0.85<br>•        | •             | Std                         | •                                 | Std        | •               | 10-Yr          |
| 0.70<br>•               | 40<br>•                      | BETTER<br>( )))    | N/A              | Class A<br>•  | 0.85<br>•        | •             | •                           | •                                 | Std        | •               | •              |
| 0.70<br>•               | 40<br>•                      | BETTER<br>( )))    | N/A              | Class A<br>•  | 0.85<br>•        | •             | Std                         | •                                 | Std        | •               | 10-Yr          |


3/4" Thick – 15/16" Angled Tegular & 9/16" Beveled Tegular

| Made-to-Order Sizes | Width     | Length    | N/A | N/A | N/A | N/A | Class A | 0.85 | • | Std | • | • | Std | • | 10-Yr |
|---------------------|-----------|-----------|-----|-----|-----|-----|---------|------|---|-----|---|---|-----|---|-------|
| CIRRUS® High CAC    | 12" - 24" | 12" - 48" |     |     |     |     |         |      |   |     |   |   |     |   |       |

1 Ctn Min  
**FASTSIZE**  
3 WEEKS  
order to ship

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).  
Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A)

**ASTM E1264 Classification**  
Type III, Form 1, Pattern E I; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard™ Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Design Considerations**  
Color ceilings are dye-lotted and should be segregated by dye lot. Do not mix. Coordinating suspension system colors are available.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS  
UL.COM/GG  
UL 2818



**Acoustic Performance**  
CAC testing conducted using Silhouette® suspension system.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

**Insulation Value**  
R Factor – 1.9 (BTU units)  
R Factor – 0.33 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
572, 576 – 1.38 lbs/SF; 40 SF/ctn  
581, 583 – 1.21 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
1 carton

**Metric Items Available**  
572M, 581M, 583M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



MINERAL FIBER – Standard