

# CIRRUS® High NRC CIRRUS®

Square Lay-in  
medium texture



**TOTAL ACOUSTICS®**  
Sound Absorption (NRC)  
+ Sound Blocking (CAC)



**SUSTAIN®**  
High Performance  
Sustainable  
Ceiling Systems



**24/7 DEFEND™**  
Solutions for Healthier,  
Safer Spaces

CONTAIN CLEAN PROTECT

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



**DESIGNFlex®**  
A New World of Choice  
for Ceiling Systems




▲ Cirrus® Square Lay-in panels with Prelude® XL® 15/16" suspension system

See more photos at:  
[armstrongceilings.com/photogallery](http://armstrongceilings.com/photogallery)

Medium-texture panels offer both Sustain® and Total Acoustics® panel performance; Good noise reduction and sound blocking in one panel.

## KEY SELECTION ATTRIBUTES

- DESIGNFlex® options include made-to-order sizes available to ship in 3 weeks
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent sustainability compliance standards today
- Refined visual
- Excellent combination of acoustical performance NRC up to 0.75 and CAC 35
-  CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- High NRC items feature Articulation Class 170, helpful to control sound over wall partitions
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 574HRC and 533HRC. 71% Pre-consumer; 15% Post-consumer
- USDA-Certified Biobased Product – 91%

## COLOR



White  
(WH)

## DETAILS



1. Cirrus® Square Lay-in
2. Cirrus® Square Lay-in with Prelude® XL® 15/16" suspension system

TechLine 877 276-7876  
[armstrongceilings.com/cirrus](http://armstrongceilings.com/cirrus)

**Armstrong®**  
CEILING & WALL SOLUTIONS

# CIRRUS® High NRC CIRRUS®

Square Lay-in  
medium texture



USDA  
CERTIFIED  
BIOBASED  
PRODUCT  
PRODUCT 91%

Declare.

SUSTAIN®  
High Performance  
Sustainable Ceiling Systems

GREENGUARD  
Gold Certified  
(details below)

LEED®  
WELL™ LBC

UP TO 87% RECYCLED  
CONTENT

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT

## VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CIRRUS® High NRC 15/16" Square Lay-in	1	563	24 x 24 x 7/8"
Made-to-Order Sizes		Width	Length
CIRRUS® High NRC		4" - 24"	4" - 48"
CIRRUS® High NRC 15/16" Square Lay-in	1	574 574HRC	24 x 24 x 3/4" 24 x 24 x 3/4"
Made-to-Order Sizes		Width	Length
CIRRUS®		12" - 24"	12" - 48"

3-4 WEEKS order to ship

1 Ctn Min FASTSIZE 3 WEEKS order to ship


## PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Durability	Recycle Program	30-Yr Warranty
0.75	35	BETTER	170	Class A	0.85	•	•	•	Std	•	•
0.75	35	BETTER	170	Class A	0.85	•	Std	•	Std	•	10-Yr
N/A	N/A	N/A	N/A	Class A	0.85	•	Std	•	Std	•	10-Yr
0.70	35	BETTER	N/A	Class A	0.85	•	•	•	Std	•	•
0.70	35	BETTER	N/A	Class A	0.85	•	Std	•	Std	•	10-Yr
N/A	N/A	N/A	N/A	Class A	0.85	•	Std	•	Std	•	10-Yr

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEM



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

**ASTM E1264 Classification**  
Type III, Form 1, Pattern E I  
Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications. Excludes items 533, 533HRC, 565, and large sizes.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustic Performance**  
CAC testing conducted using Prelude® suspension system.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

**Insulation Value**  
R Factor – 1.9 (BTU units); R Factor – 0.33 (Watts units)

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
533, 533HRC, 565 – 1.21 lbs/SF; 48 SF/ctn  
563 – 1.33 lbs/SF; 40 SF/ctn  
574, 574HRC – 1.10 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
1 carton, excludes Cirrus® High NRC panels

**Metric Items Available**  
574M, 533M, 563M, 565M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



MINERAL FIBER – Standard