

# DESIGNER™

Square Lay-in & Tegular  
coarse texture

**LEED® WELL | LBC**  
UP TO **42% RECYCLED CONTENT**

energy management  
construction waste mgmt  
regional materials  
design for flexibility  
EPD  
recyclable/producer resp.  
biobased materials  
recycled content  
sourcing of raw materials  
material ingredient reporting  
low emitting materials  
lighting quality  
acoustics

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT

\$\$\$\$



Coarse-texture panels; Economical option with standard acoustical performance.

### KEY SELECTION ATTRIBUTES

- Standard sound absorption
- Cost-effective

### COLOR



White (Wh)

▲ Designer™ Lay-in panels with Prelude® XL® 15/16" suspension system

### VISUAL SELECTION

armstrongceilings.com/catdws	Susp. Dwg.	Item No.	Dimensions (Inches)
DESIGNER™ 15/16" Square Lay-in	1	735	24 x 24 x 5/8" <input type="checkbox"/>
		734	24 x 48 x 5/8" <input type="checkbox"/>
15/16" Angled Tegular	13	737	24 x 24 x 5/8" <input type="checkbox"/>


### PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =										
0.55 30	N/A	Class A	0.81	N/A	Std	N/A	Std	Std	•	1-Yr
0.55 30	N/A	Class A	0.81	N/A	Std	N/A	Std	Std	•	1-Yr
0.55 33	N/A	Class A	0.81	N/A	Std	N/A	Std	Std	•	1-Yr

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

### SUSPENSION SYSTEMS



### PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

**ASTM E1264 Classification**  
Type III, Form 2, Pattern F; Fire Class A

**Humidity/Sag Resistance**  
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

**Insulation Value**  
R Factor – 1.5 (BTU units)  
R Factor – 0.26 (Watts units)

**1-Year Limited Warranty**  
Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight; Square Feet/Carton**  
734 – 0.80 lbs/SF; 80 SF/ctn  
735, 737 – 0.80 lbs/SF; 64 SF/ctn

**Minimum Order Quantity**  
1 carton

**Metric Items Available**  
735M, 734M, 737M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.