

RANDOM FISSURED™

Square Lay-in
medium texture

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



▲ Random Fissured™ panels with Prelude® XL® 15/16" suspension system

Economical, medium-textured panels with an easy-to-clean, durable surface that offer standard to good sound absorption.

KEY SELECTION ATTRIBUTES

- High sound absorption (perforated panels only)
- Easy-to-clean, durable surface – Impact-, Scratch-, and Soil-resistant, and scrubbable
- Economical
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR



White
(WH)

RANDOM FISSURED™

Square Lay-in
medium texture

LEED® WELL™ LBC



UP TO **71% RECYCLED CONTENT**

energy management construction waste mgmt regional materials design for flexibility EPD recyclable/pre-consumer producer resp. biobased materials recycled content sourcing of raw materials material ingredient reporting low emitting materials lighting quality acoustics

Calculate sustainability with GreenGenie™ armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
RANDOM FISSURED™ (Perforated) 15/16" Square Lay-in 	1	2908	24 x 24 x 5/8" <input type="checkbox"/>
		2910	24 x 48 x 5/8" <input type="checkbox"/>
RANDOM FISSURED™ (Unperforated) 15/16" Square Lay-in 	1	2909	24 x 24 x 5/8" <input type="checkbox"/>
		2911	24 x 48 x 5/8" <input type="checkbox"/>

PERFORMANCE SELECTION

Dots represent high level of performance.


UL Classified Acoustics		Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	Water Repel	Wash	Scrub	Impact	Soil	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC =															
0.70	N/A	N/A	Class A	0.71	•	•	N/A	N/A	•	•	•	•	•	N/A	•
0.70	N/A	N/A	Class A	0.71	•	•	N/A	N/A	•	•	•	•	•	N/A	•
0.55	N/A	N/A	Class A	0.71	•	•	N/A	•	•	•	•	•	•	N/A	•
0.55	N/A	N/A	Class A	0.71	•	•	N/A	•	•	•	•	•	•	N/A	•

Made-to-Order Sizes	5/8" Thick – 15/16" Square Lay-in (Perforated & Unperforated)	Width	Length	N/A	N/A	N/A	Class A	0.71	•	•	N/A	N/A	•	•	•	•	N/A	•
		12" - 30"	12" - 60"															



¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Fiberglass with vinyl facing

Surface Finish
Scrubable vinyl film facing (UV protected)

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
2908, 2910 – Type XII, Form 1, Pattern E C
2909, 2911 – Type XII, Form 1, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value
R Factor - 2.6 (BTU units)
R Factor - 0.46 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
0.17 lbs/SF; 128 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
Items 2908M, 2910M, 2909M, 2911M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



FIBERGLASS – Standard