

# CIRRUS® Themes™ Critters™, Leaves™, Stars™, Things That Fly™ & Under the Sea™

Tegular  
medium texture



▲ Cirrus® Themes™ Critters™ panels with Suprafine® XL® 9/16" suspension system

Medium texture panels with playful designs for a fun addition to your projects.

## KEY SELECTION ATTRIBUTES

- A variety of lighthearted panel designs on classic Cirrus texture; can be spot-painted
- Coordinating plain panels available
- Mold- and mildew-resistant surface
- USDA-Certified Biobased Product – 91%

## COLOR



White  
(WH)



▲ Cirrus® Themes™ Stars™ panels with Suprafine® XL® 9/16" suspension system



▲ Cirrus® Themes™ Leaves™ panels with Suprafine® XL® 9/16" suspension system



▲ Cirrus® Themes™ Things That Fly™ panels with Suprafine® XL® 9/16" suspension system



▲ Cirrus® Themes™ Under The Sea™ panels with Suprafine® XL® 9/16" suspension system

# CIRRUS® Themes™ Critters™, Leaves™, Stars™, Things That Fly™ & Under the Sea™

Tegular  
medium texture

USDA  
CERTIFIED  
BIOBASED  
PRODUCT 91%

GREENGUARD  
Gold Certified  
(details below)

LEED® WELL™ LBC

67% RECYCLED CONTENT

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

## VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CIRRUS® Themes™ 15/16" Angled Tegular	13	See Below	24 x 24 x 3/4"
9/16" Beveled Tegular	29, 44, 48, 52, 56	See Below	24 x 24 x 3/4"

## PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$


UL Classified Acoustics	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
N/A	N/A	Class A	0.85	•	Std	•	Std	•	•	10-Yr
N/A	N/A	Class A	0.85	•	Std	•	Std	•	•	10-Yr

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

CIRRUS Themes Critters		CIRRUS Themes Leaves		CIRRUS Themes Stars			CIRRUS Themes Things That Fly			CIRRUS Themes Under the Sea		Plain Panel
												S299/S295 <b>Must use Item S295 or S299 for Coordinating Plain Panel</b>

CIRRUS Themes Critters		CIRRUS Themes Leaves		CIRRUS Themes Stars		CIRRUS Themes Things That Fly		CIRRUS Themes Under The Sea	
15/16" Angled Tegular	9/16" Beveled Tegular	15/16" Angled Tegular	9/16" Beveled Tegular	15/16" Angled Tegular	9/16" Beveled Tegular	15/16" Angled Tegular	9/16" Beveled Tegular	15/16" Angled Tegular	9/16" Beveled Tegular
S550	S500	S650	S600	S450	S400	S750	S700	S850	S800
S551	S501	S651	S601	S451	S401	S751	S701	S851	S801
S552	S502	S652	S602	S460	S410	S752	S702	S852	S802
S553	S503	S653	S603	S461	S411	S753	S703	S853	S803
S560	S510	S654	S604	S462	S412	S754	S704	S854	S804
S562	S512	S655	S605	S463	S413	S755	S705	S855	S805
S295	S299	S295	S299	S464	S414	S756	S706	S295	S299
				S470	S420	S757	S707		
				S471	S421	S758	S708		
				S295	S299	S295	S299		

## SUSPENSION SYSTEMS



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).  
Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies.

**ASTM E1264 Classification**  
Type III, Form 1, Pattern E I K Z (scored multi-patterned finish)  
S299, S295 – Type III, Form 1, Pattern E I  
Fire Class A

**Humidity/Sag Resistance**  
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
UL.COM/GG UL 2818



**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
R Factor – 1.9 (BTU units); R Factor – 0.33 (Watts units)

**Warranty**  
Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
All design panels – 1.38 lbs/SF; 8 SF/ctn  
S295 – 1.09 lbs/SF; 48 SF/ctn  
S299 – 1.17 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
1 carton

TechLine / 1 877 276-7876  
armstrongceilings.com/cirrusthemes  
BPCS-4332-1020

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a trademark of the International Living Future Institute®; WELL™ and Well Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are registered trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2020 AWI Licensing LLC

**Armstrong®**  
CEILING & WALL SOLUTIONS

MINERAL FIBER – Standard