

KITCHEN ZONE™

Square Lay-in
smooth texture



SUSTAIN®
High Performance
Sustainable
Ceiling Systems



**24/7
DEFEND™**
Solutions for Healthier,
Safer Spaces

CONTAIN CLEAN PROTECT

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



▲ Kitchen Zone™ 24" x 24" panels with Prelude® XL® 15/16" suspension system

Panels meet USDA/FSIS guidelines. A better option than vinyl-covered gypsum; Panel offers a lower cost, lighter weight option, with more pieces per carton.

KEY SELECTION ATTRIBUTES

- new** • Kitchen Zone™ panels are part of the Sustain® portfolio and meet the most stringent sustainability compliance standards today
- Easier to cut with less dust
- Recyclable through Armstrong Recycling Program
- new** • Brighter visual with 20% more light reflectance than vinyl-covered gypsum
- new** • CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Durable – Water-repellent, Washable, Scratch-resistant, Soil-resistant
- Smooth surface meets USDA/FSIS guidelines for use in food processing areas
- 30-Year Limited System Warranty against visible sag, mold, and mildew

TYPICAL APPLICATIONS

- Kitchen/food preparation areas
- Laboratories
- Cafeterias
- Lavatories/restrooms

COLOR



White
(WH)

DETAILS



1. Kitchen Zone™ Lay-in
2. Kitchen Zone™ Lay-in with Prelude® 15/16" suspension system

KITCHEN ZONE™

Square Lay-in
smooth texture



Declare.

GREENGUARD Gold Certified (details below)

LEED WELL | LBC

UP TO 36% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
KITCHEN ZONE™ 15/16" Square Lay-in	1	673	24 x 24 x 5/8"
		672	24 x 48 x 5/8"


PERFORMANCE SELECTION

Dots represent high level of performance.

NRC + CAC =		Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels		DURABILITY					Recycle Program	30-Yr Warranty
								Fog/Spray	Wipe	Water Repel	Wash	Scratch	Soil			
N/A	33	N/A	Class A	0.89	•	•	•	•	•	•	•	•	•	•	•	•
N/A	33	N/A	Class A	0.89	•	•	•	•	•	•	•	•	•	•	•	•

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less.

ASTM E1264 Classification
Type IX, Form 2, Pattern G
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Application Consideration
Not designed for use in close proximity to commercial grease ducts.

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
672 – 0.67 lbs/SF; 96 SF/ctn
673 – 0.82 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton