



CREATE™
 ULTIMA®, ULTIMA® Health Zone™, OPTIMA®
 Square Lay-in, Tegular & Vector®
 fine texture


**TOTAL
 ACOUSTICS®**
 Sound Absorption (NRC)
 + Sound Blocking (CAC)



▲ Ultima® Create!™ Vector® panels with Prelude® XL® 15/16" suspension system

armstrongceilings.com/capabilities
 See more photos at:
armstrongceilings.com/photogallery

Create your own custom design on smooth-texture panels, including Ultima®, Ultima® Health Zone™, or Optima® without detriment to Total Acoustics® panel performance. Great acoustics have never been so colorful.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Your unique visuals set the stage for a themed environment
- Flexibility to adapt different performance across lines, including Ultima®, Ultima® Health Zone™ and Optima®
- Excellent options for sound absorption – NRC 0.70 – 0.90
- The high performance benefits of Ultima or Optima fine-textured ceilings:
 - Washable, Soil-resistant (Ultima, Optima)
 - Water-repellent (Ultima Health Zone)
- Mold- and mildew-resistant surface
- Product is directional
- Custom samples available
- Can contribute to LEED® credits

CREATE YOUR OWN UNIQUE, CUSTOM CEILING VISUAL USING COLOR AND ARTWORK

Original Artwork Guidelines:

- Artwork must be vector-based
- Acceptable file types:
 - Adobe® Illustrator® – .ai
 - Encapsulated PostScript – .eps
 - Scalable Vector Graphics – .svg
- Acceptable Color Mode: CMYK

Original Digital Image Requirements:

- Image must be 150 dpi at full print size
- Acceptable file types:
 - Joint Photographic Experts Group – .jpg
 - Tagged Image File Format – .tiff

Solid Color Requirements:

- Custom colors are available
- Coordinating colors available on suspension systems and perimeter trims

TechLine 877 276-7876
armstrongceilings.com/create



 CEILING & WALL SOLUTIONS

CREATE™ ULTIMA®, ULTIMA® Health Zone™, OPTIMA®


Square Lay-in, Tegular & Vector®
fine texture

THEMES – Available on ULTIMA®, ULTIMA® Health Zone™, OPTIMA® CREATE!™ Panels

Blooms



Single Panel
Design 021




4-Panel Design
Design 022 (Add
A, B, C, or D for
individual panel
order)

Dragonflies



Single Panel
Design 051



4-Panel Design
Design 052 (Add
A, B, C, or D for
individual panel
order)

Stars



Single Panel
Design 041



Single Panel
Design 042



Single Panel
Design 043

Bubbles



Single Panel
Design 011



Single Panel
Design 012



Single Panel
Design 013

WOOD LOOKS – Available on ULTIMA Health Zone CREATE! Square Lay-in Panels Due to printing limitations, shade may vary from actual product.




Bamboo (BA)



Barnwood (BW)



Light Cherry (LC)



Oak (OK)



Walnut (WN)

CALL, DON'T FALL – Available on ULTIMA Health Zone CREATE! Square Lay-in Panels

Reinforce safety in patient rooms by printing warning messages, in any language, on ceiling panels. Custom designs are also available.



Custom Designs for CREATE!™ ceilings

Choose from the standard colors shown on the front of Create! 6" x 6" submittal samples. Keep in mind, sheen varies slightly depending on base panel selection (Ultima, Ultima Health Zone, Optima). Custom colors available.
NOTE: Replacement panels may vary slightly in color due to material variations over time. Product could have slight color variation from run to run; adequate attic stock should be ordered.



Optima® Create!™ Vector® panels with Prelude®
XL® suspension system



Ultima® Create!™ Vector® panels in Oak Wood
Looks with Prelude® XL® suspension system



Ultima® Create!™ Custom panels with Prelude®
XL® suspension system



Ultima® Create!™ Custom panels with Prelude®
XL® suspension system



CREATE™ ULTIMA®, ULTIMA® Health Zone™, OPTIMA®

Square Lay-in, Tegular & Vector®
fine texture

LEED® WELL™ LBC





UP TO **76% RECYCLED CONTENT**

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT
















VISUAL SELECTION

	Item No. ♦	Dimensions (Inches)	
ULTIMA® or OPTIMA® CREATE!™ Square Lay-in	Z1910UC1	24 x 24 x 3/4"	<input type="checkbox"/>
for 15/16" Prelude® XL® 	Z33520C1	24 x 24 x 1"	<input type="checkbox"/>
ULTIMA® CREATE!™ Tegular	Z1912UC1	24 x 24 x 3/4"	<input type="checkbox"/>
for 9/16" Silhouette® XL® ONLY; 1/4" or 1/8" Reveal			
ULTIMA® or OPTIMA® CREATE!™ Vector®	Z1920UC1	24 x 24 x 3/4"	<input type="checkbox"/>
for 15/16" Prelude XL (White only) 	Z39010C1	24 x 24 x 7/8"	<input type="checkbox"/>
ULTIMA® Health Zone™ CREATE!™ Square Lay-in	Z1935UC1_ _ ♦	24 x 24 x 3/4"	<input type="checkbox"/>
for 15/16" Prelude XL 			
ULTIMA® Health Zone™ CREATE!™ Tegular	Z1936UC1	24 x 24 x 3/4"	<input type="checkbox"/>
for 9/16" Silhouette® XL® ONLY; 1/4" or 1/8" Reveal 			

NOTE: Replacement panels may vary slightly in color due to material variations over time. Product could have slight color variation from run to run; adequate attic stock should be ordered. Ultima® Health Zone™ ceilings have different scrim surface than Ultima® or Optima® which may affect color.

PERFORMANCE SELECTION


Dots represent high level of performance.

				DURABILITY				Recycled Content		30-Yr Warranty
UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Anti-Mold/Mildew	Sag Resistant	Water Repel	Wash	Soil	Recycled Content	Recycle Program	
										
0.75 •	35 •	BETTER 	Class A	•	•	N/A	•	•	•	•
0.90 •	26	N/A	Class A	•	•	N/A	•	•	•	•
0.75 •	35 •	BETTER 	Class A	•	•	N/A	•	•	•	•
0.70 •	33	N/A	Class A	•	•	N/A	•	•	•	•
0.80 •	26	N/A	Class A	•	•	N/A	•	•	•	•
0.70 •	38 •	BETTER 	Class A	Bio-Block+	•	•	•	•	•	•
0.70 •	38 •	BETTER 	Class A	Bio-Block+	•	•	•	•	•	•


¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+) Based on image/color coverage, NRC may vary slightly.

♦ Add 2-letter color suffix to item when specifying or ordering standard Wood Looks items. (e.g., Z1935UC1 L C)


SUSPENSION SYSTEMS




Vector® Panel and Prelude® XL®
(White suspension required for Vector)



Tegular Panel and Silhouette® XL®
1/4" Reveal



Tegular Panel and Silhouette® XL®
1/8" Reveal



Lay-in Panel and Prelude® XL® or 360° Painted Grid

COLORS



Any Color Available on Suspension Systems and Perimeter Trims

PHYSICAL DATA

Material
Ultima®/Ultima® Health Zone: Wet-formed mineral fiber
Optima: Fiberglass with DuraBrite® acoustically transparent membrane with CAC-backing

Surface Finish
Factory-applied latex paint with UV printing

Fire Performance
Class A: ASTM E84 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Ultima/Ultima Health Zone: Type III, Form 2, Pattern E
Optima: Type XII, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

Acoustical Performance
CAC testing conducted using Silhouette® suspension system.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines

Insulation Value
Ultima/Ultima Health Zone: Optima:
R Factor – 1.6 (BTU units) R Factor – 4.0 (BTU units)
R Factor – 0.28 (Watts units) R Factor – 0.70 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. 1-year limited warranty on color. Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton
Ultima/Ultima Health Zone: 1.05 lbs/SF; 16 SF/ctn
Optima: 0.55 lbs/SF; 16 SF/ctn

Minimum Order Quantity
1 carton (4 pcs); order by the piece



MINERAL FIBER – Standard