

# CORTEGA® Second Look®

Tegular  
medium texture

**GREENGUARD**  
Gold Certified  
(details below)

**LEED® WELL™ | LBC**

UP TO **53% RECYCLED CONTENT**

energy management  
construction waste mgmt  
regional materials  
design for flexibility  
EPD  
recyclable/producer resp.  
biobased materials  
recycled content  
sourcing of raw materials  
material ingredient reporting  
low emitting materials  
lighting quality  
acoustics

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT




▲ Cortega® Second Look® II panels with Suprafine® XL® 9/16" suspension system

Medium-texture panels; Economical option with a scored plank option.


## KEY SELECTION ATTRIBUTES

- Economical
- Geometric Scored Visuals

## FACE VIEWS



Cortega® Second Look® I – Scoring creates nominal 12" x 12" squares



Cortega® Second Look® II – Scoring creates nominal 24" x 24" squares

## COLOR



White  
(WH)

## VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
CORTEGA® Second Look® I	11	2765	24 x 48 x 3/4"	
15/16" Angled Tegular				
CORTEGA® Second Look® II	11	2758	24 x 48 x 3/4"	
15/16" Angled Tegular		2767	24 x 48 x 3/4"	
9/16" Angled Tegular	27	2776	24 x 48 x 3/4"	

## PERFORMANCE SELECTION


Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =										
0.55 35	N/A	Class A	0.81	N/A	Std	•	Std	Std	•	1-Yr
0.55 40	N/A	Fire Guard	0.81	N/A	Std	•	Std	•	•	1-Yr
0.55 35	N/A	Class A	0.81	N/A	Std	•	Std	•	•	1-Yr
0.55 30	N/A	Class A	0.81	N/A	Std	•	Std	•	•	1-Yr

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

## SUSPENSION SYSTEMS

NOTE: 9/16" Cortega® Second Look® items are installed using Suprafine® suspension systems only.



## PHYSICAL DATA

Cortega®/Coretega Second Look®: wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

**Fire Guard:** A fire-resistive ceiling when used in applicable UL assemblies

**ASTM E1264 Classification**  
Type III, Form 2, Pattern C D

**Humidity/Sag Resistance**  
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

**VOC Emissions**  
(PB suffix items only)  
**GREENGUARD Gold Certified**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
2195, 704, 816, 703 – R Factor – 1.6 (BTU units);  
R Factor – 0.28 (Watts units)  
770, 772, 769, 773, 823, 824 – R Factor – 1.5 (BTU units);  
R Factor – 0.26 (Watts units)  
747, 2765, 2758, 2767, 2776 – R Factor – 1.5 (BTU units);  
R Factor – 0.26 (Watts units)

**PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS**  
UL.COM/GG  
UL 2818



**Weight: Square Feet/Carton**  
769 – 0.61 lbs/SF; 96 SF/ctn  
704, 2195 – 0.63 lbs/SF; 64 SF/ctn  
772, 773 – 0.63 lbs/SF; 100 SF/ctn  
703 – 0.65 lbs/SF; 80 SF/ctn  
770 – 0.69 lbs/SF; 64 SF/ctn  
816 – 1.08 lbs/SF; 48 SF/ctn  
823 – 1.09 lbs/SF; 48 SF/ctn  
747, 824 – 1.09 lbs/SF; 64 SF/ctn  
2765, 2767 – 0.73 lbs/SF; 80 SF/ctn  
2758 – 1.26 lbs/SF; 64 SF/ctn  
2776 – 0.70 lbs/SF; 80 SF/ctn

**Minimum Order Quantity**  
1 carton, excludes made-to-order: Cortega Square Lay-in or Tegular sizes

**Metric Items Available**  
770M, 824M, 769M, 773M, 772M, 2195M, 704M, 703M, 823M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

