

# INVISACOUSTICS™

Wall Panels  
smooth texture



**24/7  
DEFEND™**  
Solutions for Healthier,  
Safer Spaces

CONTAIN CLEAN PROTECT



**SUSTAIN®**  
High Performance  
Sustainable Ceiling Systems

**Declare.**

LEED® WELL | LBC

UP TO **84%** RECYCLED  
CONTENT

- ✓ energy management
- ✓ construction waste mgmt
- ✓ regional materials
- ✓ design for flexibility
- ✓ EPD
- ✓ recyclable/extended producer resp.
- ✓ biobased materials
- ✓ recycled content
- ✓ sourcing of raw materials
- ✓ material ingredient reporting
- ✓ low emitting materials
- ✓ lighting quality
- ✓ acoustics

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT




▲ InvisAcoustics™ 24" x 48" panels

Smooth-textured, hidden acoustical solution that installs directly to walls using ceiling adhesive.

## KEY SELECTION ATTRIBUTES

- InvisAcoustics™ panels are part of the Sustain® portfolio and meet the most stringent sustainability compliance standards today (white and field paintable panels only)
- Wall installation – 6' from the ground or higher
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning)
- Good acoustical absorption – NRC up to 0.75
- Field paintable panels can be sprayed same color as wall
- Smooth, clean durable finish –
  - Impact-resistant
  - Scratch-resistant
  - Soil-resistant
- Panels cut easily to fit into any space

## PANEL COLORS\*



\*NOTE: Ceiling Panels are dye-lotted and should be separated by dye lot. Do not mix.

## VISUAL SELECTION

Item No.	Dimensions (Inches)	Visual Representation
INVISACOUSTICS™ Standard Sizes 3/4" Square  (on 48" sides)	1212WH 24 x 48 x 3/4"	
3/4" Square  (on 24" sides)	1212BL* 24 x 48 x 3/4"	
3/4" Square  (on 24" sides)	1212FP 24 x 48 x 3/4"	

## PERFORMANCE

Dots represent high level of performance.

Fire Rating	Light Reflect	Anti-Mold/Mildew	Sag Resist	Certified Low VOC Emissions	CleanAssure™ Disinfectable Walls	DURABILITY				Recycle Program	10-Yr Warranty
						Impact	Scratch	Soil	Fog		
Class A	N/A	•	•	•	•	•	•	•	•	•	•
Class A	N/A	•	•	•	•	•	•	•	•	•	•
Class A	N/A	•	•	•	•	•	•	•	•	•	•

## ACOUSTICAL INFORMATION

Panel Thickness	NRC	Mounting Methods
3/4"	0.75 •	D-20
3/4"	0.70 •	A

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.  
\* Tech Black panels are not included in the Sustain® portfolio

PHYSICAL DATA: (Refer to InvisAcoustics product page in the Direct-to-Structure section)

TechLine 877 276-7876  
armstrongceilings.com/invisacoustics  
BPCS-6475-221

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are trademarks of the International Living Future Institute®; WELL™ and Well Building Standard are trademarks of the International WELL Building Institute; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2020 AWI Licensing LLC



PARTITIONS & WALLS