

TECTUM® Finale™
Acoustical Wall Panels
coarse texture



LEED® WELL™ LBC

energy management	construction waste mgmt	regional materials	design for flexibility	EPD	recyclable/extended producer resp.	biobased materials	FSC® (for wood)	recycled content	sourcing of raw materials	material ingredient reporting	low emitting materials	lighting quality	acoustics

LOCATION DEPENDENT

For LEED contribution visit armstrongceilings.com/greengenie



▲ Tectum® Finale™ Wall Panels (also available for ceiling applications)


Tectum® Finale™ high NRC walls provide durable, sustainable, acoustical solutions for a wide variety of applications.

KEY SELECTION ATTRIBUTES

- 1" thick Tectum® Finale™ wall panels with 1" factory-attached furring are now available as standard items.
- Select products included in the FAST134 program – ready to ship in 4 weeks or less
- Built-in furring pieces with factory-filled panels provide maximum sound control and install 2.5x faster than Direct-Attach for the same acoustic performance
- Excellent sound absorption – 1" panels have NRC up to 0.95 (mounting method dependent)
- Panel sizes include 24" x 48", 24" x 96", 48" x 48", and 48" x 96", with bevel on long edges, square on short sides. Custom panels are available in additional sizes and thicknesses upon request (ASQuote@armstrongceilings.com)
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (standard colors only)
- Abuse resistant for active spaces
- Can be mechanically fastened to a wide variety of surfaces including masonry, drywall, wood, and more

COLORS Due to printing limitations, shade may vary from actual product.

Standard Colors



VISUAL SELECTION

Item No. ◆	Dimensions W x L x D (Inches)	
TECTUM® Finale™ Wall Panels	8215W2L04T10_ _ _	24 x 48 x 1"
	8215W4L04T10_ _ _	48 x 48 x 1"
	8215W2L08T10_ _ _	24 x 96 x 1"
	8215W4L08T10_ _ _	48 x 96 x 1"

PERFORMANCE Dots represent high level of performance.

Fire Rating	Light Reflect	Anti-Mold/Mildew	Sag Resist	Fog	Impact	Scratch	30-Yr Warranty	DURABILITY	
								CleanAssure™ Disinfectable Panels	
Class A	Up to 0.75	•	•	•	•	•	•	(White only)	Bio-Block
Class A	Up to 0.75	•	•	•	•	•	•		Humi-Guard+
Class A	Up to 0.75	•	•	•	•	•	•		CleanAssure™ Disinfectable Panels
Class A	Up to 0.75	•	•	•	•	•	•		

ACOUSTICAL INFORMATION

Total Panel Thickness	NRC	Mounting Method
1" with integral Minwool insert & 1" furring	0.85 • 0.95	A D-20
1-1/2" with integral Minwool insert & 1" furring	N/A N/A	A D-20
2" with integral Minwool insert & 1" furring	N/A N/A	A D-20

FAST
4 WEEKS
or Less

FAST134 program items ready to ship from manufacturer in 4 weeks or less. Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134.

◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural (unpainted), TWH = White (e.g. 8215W2L04T10 I W H)
Four-sided beveled edge panels are recommended in adjoining panel installations
For special sizes, and colors, call TechLine at 1 877 276-7876.

ACCESSORIES, PANEL CONSTRUCTION DETAIL & EDGE DETAIL RECOMMENDATIONS (Tectum® Finale Ceiling panels, armstrongceilings.com/tectumfinalewalls)

PHYSICAL DATA (Tectum® Finale Ceiling panels, armstrongceilings.com/tectumfinalewalls)

