

# MESA™ /MESA™ Second Look®

Square Lay-in & Tegular  
fine texture



CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



▲ Mesa™ panels with Suprafine® XL® 9/16" suspension system

See more photos at:  
[armstrongceilings.com/photogallery](http://armstrongceilings.com/photogallery)  
SEARCH: mesa

Fine textured panels with scored visual options; Offers standard or Total Acoustics® panel performance.

## KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Mesa™ panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Fine-textured visual
- Excellent sound-blocking option
- Mold- and mildew-resistant surface
- USDA Certified Biobased Product – 100%
- Non-directional visual reduces installation time and scrap (excludes Second Look panels)
- Product can be recycled through the Armstrong Ceilings Recycling Program
- 30-Year Limited System Warranty against visible sag, mold, and mildew

## COLOR



White  
(WH)

## FACE VIEW



Mesa™ Second Look® II panel – Scoring created nominal 24" x 24" squares

**DETAILS** (Other Suspension Systems compatible. Refer to listing on next page.)



1. Mesa™
2. Mesa™ with Suprafine® 9/16" suspension system

# MESA™ /MESA™ Second Look®

Square Lay-in & Tegular  
fine texture

USDA  
CERTIFIED  
BIOBASED  
PRODUCT  
PRODUCT 100%

SUSTAIN™  
High Performance  
Sustainable Ceiling Systems

Declare.

GREENGUARD  
Gold Certified  
(details below)

LEED®  
WELL™ | LBC














UP TO 56% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/pre-consumer producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with GreenGenie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT

## VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
MESA™ 15/16" Square Lay-in 	1	680	24 x 24 x 3/4" 
		683	24 x 48 x 3/4" 
15/16" Angled Tegular 	13	681	24 x 24 x 3/4" 
		686	24 x 24 x 3/4" 
		684	24 x 48 x 3/4" 
9/16" Beveled Tegular 	29, 44, 48, 52, 56	682	24 x 24 x 3/4" 
		687	24 x 24 x 3/4" 
		685	24 x 48 x 3/4" 
Made-to-Order Sizes MESA™	4-6 WEEKS order to ship	Width	Length
		12" - 30"	18" - 72"
MESA™ Second Look® II 15/16" Angled Tegular 	11	688	24 x 48 x 3/4" 

## PERFORMANCE SELECTION


Dots represent high level of performance.

UL Classified Acoustics	CAC	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	DURABILITY	Recycled Content	Recycle Program	30-Yr Warranty
NRC +	CAC	NRC CAC	Class	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Scratch	Recycled Content	Recycle Program	30-Yr Warranty	
0.60	33	N/A	Class A	0.85	•	•	•	•	•	•	•
0.60	33	N/A	Class A	0.85	•	•	•	•	•	•	•
0.60	35	GOOD	Class A	0.85	•	•	•	•	•	•	•
0.60	40	GOOD	Class A	0.85	•	•	•	•	•	•	•
0.60	35	GOOD	Class A	0.85	•	•	•	•	•	•	•
0.60	35	GOOD	Class A	0.85	•	•	•	•	•	•	•
0.60	40	GOOD	Class A	0.85	•	•	•	•	•	•	•
0.60	35	GOOD	Class A	0.85	•	•	•	•	•	•	•
N/A	N/A	N/A	Class A	0.85	•	•	•	•	•	•	•
0.60	35	GOOD	Class A	0.85	•	•	•	•	•	•	•

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS

NOTE: It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

**ASTM E1264 Classification**  
Type III, Form 2, Pattern C E; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



**Acoustical Performance**  
CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

## Design Consideration

Do not mix Mesa™ Second Look® panels with standard Mesa panels in the same room. It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
680, 681, 682 – 1.02 lbs/SF; 48 SF/ctn  
683, 684, 685 – 1.02 lbs/SF; 64 SF/ctn  
686, 687 – 1.40 lbs/SF; 48 SF/ctn  
688 – 1.02 lbs/SF; 64 SF/ctn

**Minimum Order Quantity**  
1 carton

**Metric Items Available**  
680M, 683M, 682M, 681M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



MINERAL FIBER – Standard