



## ULTIMA+ dB



OFFICE – Trade Center Weena Plaza (NL)  
ULTIMA+ dB SL2

ULTIMA+ dB not only offers a finely textured and durable surface with a brighter “blue-white” colour for high light reflectance, but is also C2C Bronze certified and provides higher levels of sound attenuation performance for improving the privacy between adjacent spaces.

### Key features

- Eliminates the need for sound barriers in closed offices
- Very high light reflectance: 87%
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee

























### Application areas

Ideal for individual / private offices.



Inspiring Great Spaces®

**Armstrong®**  
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	SL2								
												
<b>THICKNESS (mm)</b>	<b>19</b>	<b>19</b>	<b>19</b>	<b>23</b>								
<b>MODULES (mm)</b>	600 x 600 ..... 7688M 625 x 625 ..... 7688D 675 x 675 ..... 7689M 1200 x 600 ..... 7690M	600 x 600 ..... 7695M 625 x 625 ..... 7695D 675 x 675 ..... 7696M	600 x 600 ..... 7697M 625 x 625 ..... 7697D 675 x 675 ..... 7698M	1500 x 300 ..... 7691M 1800 x 300 ..... 7692M 2500 x 300 ..... 7693M								
<b>SUSPENSION SYSTEMS</b>	Prelude 24 XL <sup>2</sup> / TL <sup>2</sup> Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TL <sup>2</sup>	Prelude 24 XL <sup>2</sup> / TL <sup>2</sup> Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TL <sup>2</sup>	Prelude 15 TL / XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette 6mm XL <sup>2</sup>	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar								
<b>COLOURS</b>	 Global White											
<b>SUSTAINABILITY</b>	   											
	<sup>1</sup> Depends on thickness, edge detail and size of tile.											
<b>ACOUSTICS</b>												
	<b>Hz <math>\alpha_p</math></b>											
		<b>D<sub>nfw</sub></b>	<b>R<sub>w</sub></b>	<b><math>\alpha_w</math></b>	<b>Class</b>	<b>NRC</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>4000</b>
• Board, Tegular, MicroLook 90		<b>41 dB</b>	<b>21 dB</b>	<b>0.60(H)</b>	C	0.65	0.25	0.35	0.55	0.80	0.90	0.95
• SL2		<b>43 dB</b>	-	<b>0.60(H)</b>	C	0.55	0.35	0.40	0.50	0.60	0.75	0.85
<b>FIRE REACTION</b>		EEA Euroclass A2-s1, d0 EN 13501-1				RUS KM1 (G1, V1, D1, T1) FZ 123						
<b>OTHER PERFORMANCES &amp; FEATURES</b>	 87%	 95% RH	 ISO 5					 30 YEAR system guarantee		 BIM READY		
	 $\lambda = 0.067 \text{ W/m K}$ EN 12667 & ISO 8301	 7.6 kg/m <sup>2</sup> (Board, Tegular, MicroLook 90) 9.1 kg/m <sup>2</sup> (SL2)	 ISO 14644-1									
<b>CUSTOM OPTIONS</b>	 Dimensions											